

LEIPA Shine

CEPI-Code 73 Tentative specification

LEIPA Shine is part of our comprehensive range of packaging papers suitable for the corrugated production. It is a double coated white top testliner based on 100% recycled waste paper and designed for great print results in offset printing. LEIPA Shine's homogeneous surface guarantees excellent contrasts.

Characteristics

- » High brightness
- » Smooth and homogeneous surface
- » High contrast

Key Benefits

- » Supports the sustainable market for recovered paper
- » It will be developed for the use in offset printing and to print a wider range of colours with excellent print results

Properties	Unit	Standard	Target Figures			Tolerances
Grammage	lb/msf	ISO 536	32,8	36,9	43,1	± 4%
Moisture	%	ISO 287	6,5	6,5	6,5	± 1,0
Burst resistance	psi	ISO 2759	44,2	50,8	55,1	- 10%
SCT CD	lbf/in	ISO 9895	13,1	15,4	18,3	- 1,7
	kNm/kg	ISO 9895	14,4	15,0	15,2	
Cobb60 (top side)	g/m ²	ISO 535	35	35	35	≤ 50
Brightness (top side)	%	ISO 2470-2	87	87	87	- 1
Roughness PPS (top side)	µm	ISO 8791-4	1,9	2,0	2,5	+ 0,7
Caliper	µm	ISO 534	165	185	215	± 5%

All values are measured under standard climate condition (23°C, 50% RH). Our measurement devices are included within the CEPI cycle.

Certifications



Are you interested? Please contact us.

www.leipa.com/packagingpaper
sales@leipa.com
 +49 3332 24-3000

