leipa packaging paper

LEIPA Classic brown *CEPI-Code 30*

LEIPA Classic brown is part of our comprehensive range of packaging papers suitable for the corrugated production. LEIPA Classic brown is a double layer testliner based on recycled paper. A performance grade produced with runnability in mind and exhibits an ideal haptic effect. The good surface coupled with high strength properties result in efficient production.

Characteristics

- High surface properties
- Ideal haptic properties
- Top printability performance
- High strength

Key Benefits

- Fulfilling high demand area
- Top runnability
- Supports the market for recovered paper
- Encourages efficient corrugated production

Typical Applications

- Retail shelf ready
- Food packaging
- Industrial packaging
- All application areas harmonising recycled fibre and high strength properties

Properties	Unit	Standard	Target Figures				Tolerances
Grammage	g/m^2	ISO 536	100	115	120	135	± 3%
Moisture	%	ISO 287	8.0	8.0	8.0	8.0	± 1
Burst resistance	kPa	ISO 2759	240	250	265	300	- 10%
SCT CD	kN/m	ISO 9895	1.7	1.9	2.1	2.3	- 0.3
Cobb60 (top side)	g/m^2	ISO 535	35	35	35	35	≤ 50
Roughness Bendtsen (top side)	ml/min	ISO 8791-2	1000	1100	1100	1200	+ 100

All values are measured under standard climate condition (23°C, 50% RH). Our measurement devices are included within the CEPI cycle.

Certifications

FSC www.fsc.org FSC® C089451 The mark of responsible forestry

PEFC PEFC/04-31-0619 Promoting Sustainable Forest Management www.pefc.co.uk

Are you interested? Please contact us.

www.leipa.com/packagingpaper
sales@leipa.com
+49 3332 24-3000

Specification valid from September 2026